



POLYMER NATION

Safety Data Sheet F-01 Part A

SECTION 1: Identification

1.1 GHS Product identifier

Product name	F-01 Part A
Product number	E1
Brand	Polymer Nation

1.2 Other means of identification

Epoxy Resin

1.3 Recommended use of the chemical and restrictions on use

100% solids clear epoxy resin for use in resinous flooring applications

1.4 Supplier's details

Name	Polymer Nation
Address	405 Oakwood Ave
	Waukegan IL 60085

Telephone 847-774-5038

1.5 Emergency phone number

800-424-9300

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2024)

- Hazardous to the aquatic environment, long-term (chronic), Cat. 2
- Eye damage/irritation, Cat. 2A
- Toxic to reproduction, Cat. 1B
- Skin corrosion/irritation, Cat. 2

2.2 GHS label elements, including precautionary statements

Pictograms



Signal word

Danger

Safety Data Sheet

F-01 Part A

Hazard statement(s)

H315	Causes skin irritation
H319	Causes serious eye irritation
H360	May damage fertility or the unborn child [effect, route]
H411	Toxic to aquatic life with long lasting effects

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P264	Wash ... thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water/...
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see ... on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container to ...

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

1. EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule weight

Concentration	80 - 90 % (weight)
EC no.	500-033-5
CAS no.	25068-38-6
Index no.	603-074-00-8

- Skin corrosion/irritation, Cat. 2
- Eye damage/irritation, Cat. 2A
- Sensitization, skin, Cat. 1
- Hazardous to the aquatic environment, long-term (chronic), Cat. 2

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects
SCLs/M-factors/ATEs	Eye Irrit. 2; H319: C ≥ 5% Skin Irrit. 2; H315: C ≥ 5%

2. Alkyl epoxy resin

Concentration	1 - 10 % (weight)
EC no.	271-846-8
CAS no.	68609-97-2
Index no.	603-103-00-4

Safety Data Sheet

F-01 Part A

- Skin corrosion/irritation, Cat. 2
- Sensitization, skin, Cat. 1

H315 Causes skin irritation
H317 May cause an allergic skin reaction

3. Component 3 (trade secret)*

Concentration 1 - 10 % (weight)

- Skin corrosion/irritation, Cat. 2
- Sensitization, skin, Cat. 1

H315 Causes skin irritation
H317 May cause an allergic skin reaction

4. TETRAHYDROFURFURYL ALCOHOL

Concentration 1 - 5 % (weight)

EC no. 202-625-6

CAS no. 97-99-4

Index no. 603-061-00-7

- Toxic to reproduction, Cat. 1B
- Eye damage/irritation, Cat. 2A

H319 Causes serious eye irritation
H360Df May damage the unborn child. Suspected of damaging fertility.

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

If inhaled

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

In case of skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

In case of eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

Safety Data Sheet

F-01 Part A

If swallowed

Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Personal protective equipment for first-aid responders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of immediate medical attention and special treatment needed, if necessary

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).

Unsuitable extinguishing media: Do not use water jet

5.2 Specific hazards arising from the chemical

Carbon oxides
carbon dioxide
carbon monoxide
halogenated compounds

In a fire or if heated, a pressure increase will occur and the container may burst.

5.3 Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

Safety Data Sheet

F-01 Part A

inadequate. Put on appropriate personal protective equipment.

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Keep container tightly closed and sealed

Safety Data Sheet

F-01 Part A

until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule wei (CAS: 25068-38-6 EC: 500-033-5)
2. Alkyl epoxy resin (CAS: 68609-97-2 EC: 271-846-8)
3. TETRAHYDROFURFURYL ALCOHOL (CAS: 97-99-4 EC: 202-625-6)

8.2 Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Thermal hazards

No data available

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental

Safety Data Sheet

F-01 Part A

protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state	Liquid
Appearance	clear
Odor	mild
Odor threshold	ND
Melting point/freezing point	ND
Boiling point or initial boiling point and boiling range	395.6 F/202 C
Flammability	ND
Lower and upper explosion limit/flammability limit	ND
Flash point	485 F/251.6 C
Auto-ignition temperature	ND
Decomposition temperature	ND
pH	ND
Kinematic viscosity	<1000 cP
Solubility	ND
Partition coefficient n-octanol/water (log value)	ND
Vapor pressure	ND
Evaporation rate	ND
Density and/or relative density	1.12
Relative vapor density	ND

SECTION 10: Stability and reactivity

10.1 Reactivity

None under normal use conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

None under normal use conditions.

10.4 Conditions to avoid

Strong oxidizer

10.5 Incompatible materials

No specific data.

10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, oxides of nitrogen, other undetermined compounds

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Alkyl epoxy resin

LD50 Oral - Rat - 1163 mg/kg

Safety Data Sheet

F-01 Part A

LD50 Skin - Rabbit - 1130 mg/kg

LC50 Inhalation - Rat - >11.3 mg/l

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule weight 394.4

LD50 Skin - Rat - 2,000 mg/kg

LD50 Oral - Rat - 11,400 mg/kg

TETRAHYDROFURFURYL ALCOHOL

LD50 Oral - Rat - >2000 mg/kg

Skin corrosion/irritation

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN)

Rabbit

Result: Score 1.5 - 2

Remarks: Skin -Erythema/Eschar 404

Acute Dermal Irritation/Corrosion

Rabbit

Result: Score 1.0 - 1.5

Remarks: Skin -Edema 404

Acute Dermal Irritation/Corrosion

Rabbit - 24 hrs

Remarks: Skin -Moderate irritant

Serious eye damage/irritation

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN)

Rabbit

Remarks: eyes - Mild irritant

Respiratory or skin sensitization

Skin sensitizer

In an OECD No. 429 mouse LLNA study the estimated EC3 was a concentration of 5.7% suggesting that BADGE is a moderate skin sensitizer in this test system.

In an OECD No. 406 guinea pig Maximization study BADGE induced positive dermal reaction in 100% of the test animals at a 50% concentration challenge dose. Therefore, BADGE is an "Extreme" skin sensitizer under the conditions of this study. BADGE was also positive for skin sensitization in an OECD No. 406 guinea pig Buehler method study.

Germ cell mutagenicity

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN),

Remarks: Did not induce evidence of chromosome damage in a mouse dominant lethal oral gavage study conducted up to a high dose level of 10 grams/kg and in a mouse micronucleus test conducted up to a high dose of 5000 mg/kg. Negative in a male mouse spermatocyte cytogenetic assay with treatment for 5 days by oral gavage up to a high dose of 3000 mg/kg. Did not induce an increase in the frequency of chromosome damage in a Chinese hamster bone marrow cytogenetic test by oral gavage up to a high dose of 3300 mg/kg. Failed to induce an increase of DNA strand breaks in rat liver cells following oral gavage treatment with 500 mg/kg as measured by alkaline elution.

Carcinogenicity

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Safety Data Sheet

F-01 Part A

Reproductive toxicity

Based on available data, classification data are not met

Specific target organ toxicity (STOT) - single exposure

No data available

Specific target organ toxicity (STOT) - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

Toxicity

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule weight

LC50 - Fish - 1.3 mg/l - 96 h

EC50 - Daphnia magna (water flea) - 2.1 mg/l - 48 h

LC50 - Algae - >11 mg/l - 72 h

Persistence and degradability

No data available on product

Bioaccumulative potential

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN),

Remarks: LogPow 2.64 3.78

BCF 3-31 31.00

Potential - low

Mobility in soil

No data available on product.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Safety Data Sheet

F-01 Part A

Packaging disposal

Recondition or dispose of empty container in accordance with governmental regulations. Do not reuse empty container without proper cleaning. Empty containers retain product residue (dust, liquid, vapor and/or gases) and can be dangerous. Do not heat or cut container with electric or gas torch.

SECTION 14: Transport information

DOT (US)

UN Number: UN3082

Class: 9

Packing Group: III

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (EPOXY RESIN)

Reportable quantity (RQ):

Marine pollutant: Yes

Poison inhalation hazard:

IMDG

UN Number: UN3082

Class: 9

Packing Group: III

EMS Number:

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (EPOXY RESIN)

IATA

UN Number: UN3082

Class: 9

Packing Group: III

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (EPOXY RESIN)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Canadian Domestic Substances List (DSL)

Chemical name: Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane

CAS number: 25068-38-6

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule wei

CAS number: 25068-38-6

US EPA TSCA public inventory

Chemical name: EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule wei

CAS number: 25068-38-6

Canadian Domestic Substances List (DSL)

Chemical name: Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

CAS number: 68609-97-2

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: Alkyl epoxy resin

CAS number: 68609-97-2

Safety Data Sheet

F-01 Part A

US EPA TSCA public inventory

Chemical name: Alkyl epoxy resin
CAS number: 68609-97-2

Canadian Domestic Substances List (DSL)

Chemical name: Oxirane, 2,2'-(2,2-dimethyl-1,3-propanediyl)bis(oxymethylene)]bis-
CAS number: 17557-23-2

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: Component 3
CAS number: 17557-23-2

US EPA TSCA public inventory

Chemical name: Component 3
CAS number: 17557-23-2

Pennsylvania Right To Know Components

Chemical name: 2-FURANMETHANOL, TETRAHYDRO-
CAS number: 97-99-4

Canadian Domestic Substances List (DSL)

Chemical name: 2-Furanmethanol, tetrahydro-
CAS number: 97-99-4

EU Cosmetics Prohibited Substances List, (EC) 2009/1223 Annex II

Chemical name/INN: TETRAHYDROFURFURYL ALCOHOL
CAS number: 97-99-4

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: TETRAHYDROFURFURYL ALCOHOL
CAS number: 97-99-4

US EPA TSCA public inventory

Chemical name: TETRAHYDROFURFURYL ALCOHOL
CAS number: 97-99-4

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: TETRAHYDROFURFURYL ALCOHOL
CAS number: 97-99-4

SECTION 16: Other information

16.1 Further information/disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



POLYMER NATION

Safety Data Sheet F-00, -01 Standard Set Part B

SECTION 1: Identification

1.1 GHS Product identifier

Product name F-00, -01 Standard Set Part B
Product number H1
Brand Polymer Nation

1.2 Other means of identification

Epoxy Hardener

1.3 Recommended use of the chemical and restrictions on use

100% solids clear epoxy hardener for use in resinous flooring applications

1.4 Supplier's details

Name Polymer Nation
Address 405 Oakwood Ave
Waukegan IL 60085
Telephone 847-774-5038

1.5 Emergency phone number

800-424-9300

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2024)

- Acute toxicity, inhalation, Cat. 4
- Acute toxicity, oral, Cat. 4
- Acute toxicity, dermal, Cat. 4
- Eye damage/irritation, Cat. 1
- Sensitization, respiratory, Cat. 1
- Skin corrosion/irritation, Cat. 1B
- Sensitization, skin, Cat. 1
- Specific target organ toxicity (single exposure), Cat. 3
- Specific target organ toxicity (repeated exposure), Cat. 1

2.2 GHS label elements, including precautionary statements

Pictograms



Signal word

Danger

**Safety Data Sheet
F-00, -01 Standard Set Part B**

Hazard statement(s)

H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H372	Causes damage to organs [organs] through prolonged or repeated exposure [route]

Precautionary statement(s)

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	[In case of inadequate ventilation] wear respiratory protection.
P301+P312	IF SWALLOWED: Call a POISON CENTER /doctor/...if you feel unwell,
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of water/...
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/...
P312	Call a POISON CENTER/doctor/... if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see ... on this label).
P330	Rinse mouth.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...
P362+P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to ...

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

1. 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Concentration	25 - 50 % (weight)
EC no.	220-666-8
CAS no.	2855-13-2
Index no.	612-067-00-9

Safety Data Sheet

F-00, -01 Standard Set Part B

- Acute toxicity, oral, Cat. 4
- Skin corrosion/irritation, Cat. 1B
- Eye damage/irritation, Cat. 1
- Sensitization, skin, Cat. 1A

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
SCLs/M-factors/ATEs	Oral: ATE = 1030 mg/kg bw Skin Sens. 1A; H317: C ≥ 0,001 %

2. Benzyl alcohol

Concentration	25 - 50 % (weight)
EC no.	202-859-9
CAS no.	100-51-6
Index no.	603-057-00-5

- Acute toxicity, oral, Cat. 4
- Eye damage/irritation, Cat. 2A
- Sensitization, skin, Cat. 1B

H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
SCLs/M-factors/ATEs	oral: ATE = 1200 mg/kg bw

3. Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer

Concentration	1 - 10 % (weight)
CAS no.	68609-08-5

4. Triethanolamine

Concentration	1 - 5 % (weight)
EC no.	203-049-8
CAS no.	102-71-6

5. 4-TERT-BUTYL PHENOL

Concentration	1 - 5 % (weight)
EC no.	202-679-0
CAS no.	98-54-4
Index no.	604-090-00-8

- Toxic to reproduction, Cat. 2
- Skin corrosion/irritation, Cat. 2
- Eye damage/irritation, Cat. 1
- Hazardous to the aquatic environment, long-term (chronic), Cat. 1

H315	Causes skin irritation
H318	Causes serious eye damage
H361f	
H410	Very toxic to aquatic life with long lasting effects
SCLs/M-factors/ATEs	M=1

Safety Data Sheet

F-00, -01 Standard Set Part B

6. Xylylenediamine

Concentration 1 - 5 % (weight)
EC no. 216-032-5
CAS no. 1477-55-0

7. 1,3-Cyclohexanedimethanamine

Concentration 1 - 5 % (weight)
EC no. 219-941-5
CAS no. 2579-20-6

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	If inhaled, remove to fresh air.
In case of skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Take victim immediately to hospital.
In case of eye contact	In case of contact, immediately flush eyes with plenty of water for at least 30 minutes. If easy to do, remove contact lens, if worn. Continue rinsing eyes during transport to hospital. Protect unharmed eye. Keep eye wide open while rinsing.
If swallowed	Rinse mouth with water. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

Personal protective equipment for first-aid responders

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of immediate medical attention and special treatment needed, if necessary

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**Safety Data Sheet
F-00, -01 Standard Set Part B**

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Specific hazards arising from the chemical

Burning produces irritant fumes.

Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Unsuitable extinguishing media: Do NOT use water jet.

In the event of fire and/or explosion do not breathe fumes.

Prevent fire extinguishing water from contaminating surface water or the ground water system.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Local authorities should be advised if significant spillages cannot be contained.

Do not allow contact with soil, surface or ground water.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Wear personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes.

Use only with adequate ventilation.

Do not breathe vapours/dust.

To avoid spills during handling keep bottle on a metal tray.

Dispose of rinse water in accordance with local and national regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not

be employed in any process in which this mixture is being used.

7.2 Conditions for safe storage, including any incompatibilities

Store in original container.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions.

Safety Data Sheet

F-00, -01 Standard Set Part B

Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability: No decomposition if stored and applied as directed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Triethanolamine (CAS: 102-71-6 EC: 203-049-8)

PEL (Inhalation): 5 mg/m³; US (Cal/OSHA)

California permissible exposure limits for chemical contaminants (Title 8, Article 107)

TWA (Inhalation): 5 mg/m³; AU (AU/SWA)

Other advisory: Sen

2. Xylylenediamine (CAS: 1477-55-0)

TWA [m-Xylene-alpha,alpha'-diamine] (Inhalation): 0.1 Peak limitation mg/m³; AU (AU/SWA)

Other advisory: Sk

3. Benzyl alcohol (CAS: 100-51-6 EC: 202-859-9)

TWA: 10 ppm

US WEEL

8.2 Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Thermal hazards

No data available

Safety Data Sheet

F-00, -01 Standard Set Part B

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state	Liquid
Appearance	clear
Color	straw; yellow
Odor	amine
Odor threshold	ND
Melting point/freezing point	ND
Boiling point or initial boiling point and boiling range	ND
Flammability	ND
Lower and upper explosion limit/flammability limit	ND
Flash point	> 201 F/> 94 C
Auto-ignition temperature	ND
Decomposition temperature	ND
pH	ND
Kinematic viscosity	< 200 cP @ 72 F
Solubility	water - negligible
Partition coefficient n-octanol/water (log value)	ND
Vapor pressure	ND
Evaporation rate	ND
Density and/or relative density	1.02 g/cm3
Relative vapor density	ND

SECTION 10: Stability and reactivity

10.1 Reactivity

None under normal use conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

None under normal use conditions.

10.4 Conditions to avoid

Strong oxidizer

10.5 Incompatible materials

No specific data.

Benzyl alcohol: Strong oxidizing agents

Triethanolamine: Acids, Oxidizing agents

10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, oxides of nitrogen, other undetermined compounds

Safety Data Sheet

F-00, -01 Standard Set Part B

Benzyl alcohol: Other decomposition products - No data available
In the event of fire: see section 5

Triethanolamine: Hazardous decomposition products formed under fire conditions. - Carbon oxides, Nitrogen oxides (NOx)
Other decomposition products - No data available
In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Benzyl alcohol: LD50 Oral - Rat - 1,230 mg/kg
Remarks: Behavioral:Somnolence (general depressed activity). Behavioral:Excitement. Behavioral:Coma.
LD50 Oral - Rat - male - 1,620 mg/kg
Dermal: No data available
No data available

Triethanolamine

LD50 Oral - Mouse - 5,846 mg/kg
Remarks: Behavioral:Convulsions or effect on seizure threshold. Diarrhoea Kidney, Ureter, Bladder:Other changes.
LD50 Oral - Rat - 5,530 mg/kg
Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Lacrimation. Diarrhoea Skin and Appendages: Other: Hair.
LD50 Oral - Rabbit - 2,200 mg/kg
LD50 Oral - Guinea pig - 2,200 mg/kg
LD50 Skin - Rabbit - >22.5 g/kg

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

LD50 Oral - Rat - 1030 mg/kg
LD50 Skin - Rat - >2000 mg/kg
LC50 Inhalation - Rat - 5.01 mg/l - 4 h

Skin corrosion/irritation

Causes severe burns

Benzyl alcohol: Benzyl alcohol
OECD Test Guideline 404 Skin - Rabbit - 24 h
Result: No skin irritation

Serious eye damage/irritation

Causes serious eye damage.

Benzyl alcohol: Benzyl alcohol
OECD Test Guideline 405 Eyes - Rabbit - 24 h
Result: Eye irritation

Respiratory or skin sensitization

Skin sensitisation-May cause an allergic skin reaction.

Respiratory sensitisation-Not classified based on available information.

Safety Data Sheet

F-00, -01 Standard Set Part B

Benzyl alcohol: No data available.

Germ cell mutagenicity

Not classified based on available information.

Benzyl alcohol: No data available.

Carcinogenicity

Not classified based on available information.

Benzyl alcohol: IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Benzyl alcohol: No data available.

Summary of evaluation of the CMR properties

Benzyl alcohol: No data available.

Specific target organ toxicity (STOT) - single exposure

Not classified based on available information.

Benzyl alcohol: No data available.

Specific target organ toxicity (STOT) - repeated exposure

Not classified based on available information.

Benzyl alcohol: No data available.

Aspiration hazard

Not classified based on available information.

Benzyl alcohol: No data available.

SECTION 12: Ecological information

Toxicity

Benzyl Alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l

End point: mortality

Exposure time: 96 h

Test Type: static test

Analytical monitoring: no

Safety Data Sheet

F-00, -01 Standard Set Part B

GLP: no

Toxicity to fish (Chronic toxicity): NOEC: 48.897 mg/l

Exposure time: 30 d

Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 110 mg/l

End point: mortality

Exposure time: 96 h

Test Type: semi-static test

Persistence and degradability

benzyl alcohol:

Biodegradability : aerobic

Inoculum: activated sludge

Concentration: 100 mg/l

Biochemical oxygen demand

Result: Readily biodegradable.

Biodegradation: 95 %

Exposure time: 14 d

Method: OECD Test Guideline 301C

Stability in water : Degradation half life: 9 yr

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Biodegradability : aerobic

Inoculum: activated sludge

Concentration: 6.9 mg/l

Result: Not readily biodegradable.

Biodegradation: 8 %

Exposure time: 28 d

Method: Tested according to Directive 92/69/EEC.

Stability in water : Degradation half life (DT50): > 1 yr (25 °C) pH: 4 - 9

Hydrolysis: < 10 % at 50 °C(5 d)

Bioaccumulative potential

benzyl alcohol:

Bioaccumulation : Bioconcentration factor (BCF): 1.37

Remarks: Bioaccumulation is unlikely.

Partition coefficient: noctanol/water: log Pow: 1.05 (68 °F / 20 °C)

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 76.22

Remarks: Bioaccumulation is unlikely.

Partition coefficient: noctanol/water: log Pow: 0.99 (73 °F / 23 °C)

pH: 6.34

Mobility in soil

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Mobility : Medium: Air

Content: 0.02 %

Method: Calculation, Mackay Level I Fugacity Model

Safety Data Sheet

F-00, -01 Standard Set Part B

Medium: Water
Content: 99.83 %
Medium: Soil
Content: 0.08 %
Medium: Sediment
Content: 0.08 %
Distribution among environmental compartments: Koc: 928, log Koc: 2.97

SECTION 13: Disposal considerations

Disposal methods

Product disposal

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Packaging disposal

Recondition or dispose of empty container in accordance with governmental regulations. Do not reuse empty container without proper cleaning. Empty containers retain product residue (dust, liquid, vapor and/or gases) and can be dangerous. Do not heat or cut container with electric or gas torch.

SECTION 14: Transport information

DOT (US)

UN Number: UN2735
Class: 8
Packing Group: II
Proper Shipping Name: Amines, liquid, corrosive, n.o.s. (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE)
Reportable quantity (RQ):
Marine pollutant: no
Poison inhalation hazard:

IMDG

UN Number: UN2735
Class: 8
Packing Group: II
EMS Number:
Proper Shipping Name: Amines, liquid, corrosive, n.o.s. (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE)

IATA

UN Number: UN2735
Class: 8
Packing Group: II
Proper Shipping Name: Amines, liquid, corrosive, n.o.s. (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE)

**Safety Data Sheet
F-00, -01 Standard Set Part B**

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

New Jersey Right To Know Components

Common name: ISOPHORONEDIAMINE

CAS number: 2855-13-2

Canadian Domestic Substances List (DSL)

Chemical name: Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-

CAS number: 2855-13-2

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

CAS number: 2855-13-2

US EPA TSCA public inventory

Chemical name: 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

CAS number: 2855-13-2

Water hazard class (WGK, Germany)

Chemical name: 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE, CAS number: 2855-13-2

WGK hazard class: WGK 1 - Slightly hazardous to water

Pennsylvania Right To Know Components

Chemical name: BENZENEMETHANOL

CAS number: 100-51-6

SARA 302 Components

No chemicals in this material [Benzyl alcohol] are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material [Benzyl alcohol] does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard for: Benzyl alcohol.

Canadian Domestic Substances List (DSL)

Chemical name: Benzenemethanol

CAS number: 100-51-6

Water hazard class (WGK, Germany)

Chemical name: Benzyl alcohol, CAS number: 100-51-6

WGK hazard class: WGK 1 - Slightly hazardous to water

EU Cosmetics Allowed preservatives List, (EC) 2009/1223 Annex V

Chemical name: Benzyl alcohol

**Safety Data Sheet
F-00, -01 Standard Set Part B**

CAS number: 100-51-6

EU Cosmetics Restricted Substances List, (EC) 2009/1223 Annex III

Chemical name/INN: Benzyl alcohol

CAS number: 100-51-6

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: Benzyl alcohol

CAS number: 100-51-6

US EPA TSCA public inventory

Chemical name: Benzyl alcohol

CAS number: 100-51-6

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: BENZYL ALCOHOL

CAS number: (none)

Canadian Domestic Substances List (DSL)

Chemical name: Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer

CAS number: 68609-08-5

US EPA TSCA public inventory

Chemical name: Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer

CAS number: 68609-08-5

Pennsylvania Right To Know Components

Chemical name: ETHANOL, 2,2',2"-NITRILOTRIS-

CAS number: 102-71-6

SARA 302 Components

No chemicals in this material [Triethanolamine] are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material [Triethanolamine] does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Chronic Health Hazard for: Triethanolamine.

Canadian Domestic Substances List (DSL)

Chemical name: Ethanol, 2,2',2"-nitrilotris-

CAS number: 102-71-6

Water hazard class (WGK, Germany)

Chemical name: Triethanolamine, CAS number: 102-71-6

Safety Data Sheet

F-00, -01 Standard Set Part B

WGK hazard class: WGK 1 - Slightly hazardous to water

US EPA TSCA public inventory

Chemical name: Triethanolamine

CAS number: 102-71-6

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: TRIETHANOLAMINE

CAS number: 102-71-6

Canadian Domestic Substances List (DSL)

Chemical name: Phenol, 4-(1,1-dimethylethyl)-

CAS number: 98-54-4

EU Cosmetics Prohibited Substances List, (EC) 2009/1223 Annex II

Chemical name/INN: 4-TERT-BUTYL PHENOL

CAS number: 98-54-4

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: 4-TERT-BUTYL PHENOL

CAS number: 98-54-4

EU SVHC Candidate List for Authorisation

Chemical name: 4-TERT-BUTYL PHENOL

CAS number: 98-54-4

US EPA TSCA public inventory

Chemical name: 4-TERT-BUTYL PHENOL

CAS number: 98-54-4

Water hazard class (WGK, Germany)

Chemical name: 4-TERT-BUTYL PHENOL, CAS number: 98-54-4

WGK hazard class: WGK 3 - Extremely hazardous to water

New Jersey Right To Know Components

Common name: m-XYLENE alpha, alpha'-DIAMINE

CAS number: 1477-55-0

Pennsylvania Right To Know Components

Chemical name: 1,3-BENZENEDIMETHANAMINE

CAS number: 1477-55-0

Canadian Domestic Substances List (DSL)

Chemical name: 1,3-Benzenedimethanamine

CAS number: 1477-55-0

US EPA TSCA public inventory

Chemical name: Xylenediamine

CAS number: 1477-55-0

**Safety Data Sheet
F-00, -01 Standard Set Part B**

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: MXDA

CAS number: 1477-55-0

Water hazard class (WGK, Germany)

Chemical name: Xylylenediamine, CAS number: 1477-55-0

WGK hazard class: WGK 2 - Hazardous to water

Canadian Domestic Substances List (DSL)

Chemical name: 1,3-Cyclohexanedimethanamine

CAS number: 2579-20-6

US EPA TSCA public inventory

Chemical name: 1,3-Cyclohexanedimethanamine

CAS number: 2579-20-6

Water hazard class (WGK, Germany)

Chemical name: 1,3-Cyclohexanedimethanamine, CAS number: 2579-20-6

WGK hazard class: WGK 2 - Hazardous to water

SECTION 16: Other information

16.1 Further information/disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



POLYMER NATION

Safety Data Sheet F-41 Part A

SECTION 1: Identification

1.1 GHS Product identifier

Product name	F-41 Part A
Product number	E5
Brand	Polymer Nation

1.2 Other means of identification

Epoxy Resin

1.3 Recommended use of the chemical and restrictions on use

100% solids clear UV resistant epoxy resin for use in resinous flooring applications

1.4 Supplier's details

Name	Polymer Nation
Address	405 Oakwood Ave
	Waukegan IL 60085

Telephone 847-774-5038

1.5 Emergency phone number

800-424-9300

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2024)

- Hazardous to the aquatic environment, long-term (chronic), Cat. 2
- Eye damage/irritation, Cat. 2A
- Toxic to reproduction, Cat. 1B
- Skin corrosion/irritation, Cat. 2
- Sensitization, skin, Cat. 1

2.2 GHS label elements, including precautionary statements

Pictograms



Signal word

Danger

Safety Data Sheet

F-41 Part A

Hazard statement(s)

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H360	May damage fertility or the unborn child [effect, route]
H411	Toxic to aquatic life with long lasting effects

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash ... thoroughly after handling.
P272	Contaminated work clothing must not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water/...
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see ... on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container to ...

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

1. EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule weight

Concentration	80 - 90 % (weight)
EC no.	500-033-5
CAS no.	25068-38-6
Index no.	603-074-00-8

- Skin corrosion/irritation, Cat. 2
- Eye damage/irritation, Cat. 2A
- Sensitization, skin, Cat. 1
- Hazardous to the aquatic environment, long-term (chronic), Cat. 2

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects
SCLs/M-factors/ATEs	Eye Irrit. 2; H319: C ≥ 5% Skin Irrit. 2; H315: C ≥ 5%

Safety Data Sheet

F-41 Part A

2. Alkyl epoxy resin

Concentration 1 - 10 % (weight)
EC no. 271-846-8
CAS no. 68609-97-2
Index no. 603-103-00-4

- Skin corrosion/irritation, Cat. 2
- Sensitization, skin, Cat. 1

H315 Causes skin irritation
H317 May cause an allergic skin reaction

3. Component 3 (trade secret)*

Concentration 1 - 10 % (weight)

- Skin corrosion/irritation, Cat. 2
- Sensitization, skin, Cat. 1

H315 Causes skin irritation
H317 May cause an allergic skin reaction

4. TETRAHYDROFURFURYL ALCOHOL

Concentration 1 - 5 % (weight)
EC no. 202-625-6
CAS no. 97-99-4
Index no. 603-061-00-7

- Toxic to reproduction, Cat. 1B
- Eye damage/irritation, Cat. 2A

H319 Causes serious eye irritation
H360Df May damage the unborn child. Suspected of damaging fertility.

5. Component 5 (trade secret)*

Concentration 1 - 3 % (weight)

6. Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidinyl) ester

Concentration 1 % (weight)
EC no. 280-060-4
CAS no. 82919-37-7

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

If inhaled

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call

Safety Data Sheet

F-41 Part A

a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

In case of skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

In case of eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

If swallowed

Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Personal protective equipment for first-aid responders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of immediate medical attention and special treatment needed, if necessary

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).

Unsuitable extinguishing media: Do not use water jet

5.2 Specific hazards arising from the chemical

Carbon oxides
carbon dioxide
carbon monoxide
halogenated compounds

Safety Data Sheet

F-41 Part A

In a fire or if heated, a pressure increase will occur and the container may burst.

5.3 Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Safety Data Sheet

F-41 Part A

Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule wei (CAS: 25068-38-6 EC: 500-033-5)
2. Alkyl epoxy resin (CAS: 68609-97-2 EC: 271-846-8)
3. TETRAHYDROFURFURYL ALCOHOL (CAS: 97-99-4 EC: 202-625-6)

8.2 Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be

Safety Data Sheet

F-41 Part A

noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Thermal hazards

No data available

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state	Liquid
Appearance	clear
Odor	mild
Odor threshold	ND
Melting point/freezing point	ND
Boiling point or initial boiling point and boiling range	395.6 F/202 C
Flammability	ND
Lower and upper explosion limit/flammability limit	ND
Flash point	485 F/251.6 C
Auto-ignition temperature	ND
Decomposition temperature	ND
pH	ND
Kinematic viscosity	<1000 cP
Solubility	ND
Partition coefficient n-octanol/water (log value)	ND
Vapor pressure	ND
Evaporation rate	ND
Density and/or relative density	1.12
Relative vapor density	ND

SECTION 10: Stability and reactivity

10.1 Reactivity

None under normal use conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

None under normal use conditions.

Safety Data Sheet

F-41 Part A

10.4 Conditions to avoid

Strong oxidizer

10.5 Incompatible materials

No specific data.

10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, oxides of nitrogen, other undetermined compounds

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Alkyl epoxy resin

LD50 Oral - Rat - 1163 mg/kg

LD50 Skin - Rabbit - 1130 mg/kg

LC50 Inhalation - Rat - >11.3 mg/l

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN)

LD50 Skin - Rat - 2,000 mg/kg

LD50 Oral - Rat - 11,400 mg/kg

TETRAHYDROFURFURYL ALCOHOL

LD50 Oral - Rat - >2000 mg/kg

Skin corrosion/irritation

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN)

Rabbit

Result: Score 1.5 - 2

Remarks: Skin - Erythema/Eschar 404

Acute Dermal Irritation/Corrosion

Rabbit

Result: Score 1.0 - 1.5

Remarks: Skin - Edema 404

Acute Dermal Irritation/Corrosion

Rabbit - 24 hrs

Remarks: Skin - Moderate irritant

Serious eye damage/irritation

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN)

Rabbit

Remarks: eyes - Mild irritant

Respiratory or skin sensitization

Skin sensitizer

In an OECD No. 429 mouse LLNA study the estimated EC3 was a concentration of 5.7% suggesting that BADGE is a moderate skin sensitizer in this test system.

In an OECD No. 406 guinea pig Maximization study BADGE induced positive dermal reaction in 100% of the test animals at a 50% concentration challenge dose. Therefore, BADGE is an "Extreme" skin sensitizer under the conditions of this study. BADGE was also positive for skin sensitization in an OECD No. 406 guinea pig Buehler method study.

Safety Data Sheet

F-41 Part A

Germ cell mutagenicity

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN),

Remarks: Did not induce evidence of chromosome damage in a mouse dominant lethal oral gavage study conducted up to a high dose level of 10 grams/kg and in a mouse micronucleus test conducted up to a high dose of 5000 mg/kg. Negative in a male mouse spermatocyte cytogenetic assay with treatment for 5 days by oral gavage up to a high dose of 3000 mg/kg. Did not induce an increase in the frequency of chromosome damage in a Chinese hamster bone marrow cytogenetic test by oral gavage up to a high dose of 3300 mg/kg. Failed to induce an increase of DNA strand breaks in rat liver cells following oral gavage treatment with 500 mg/kg as measured by alkaline elution.

Carcinogenicity

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Reproductive toxicity

Based on available data, classification data are not met

Specific target organ toxicity (STOT) - single exposure

No data available

Specific target organ toxicity (STOT) - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

Toxicity

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule weight

LC50 - Fish - 1.3 mg/l - 96 h

EC50 - Daphnia magna (water flea) - 2.1 mg/l - 48 h

LC50 - Algae - >11 mg/l - 72 h

Persistence and degradability

No data available on product

Bioaccumulative potential

EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN),

Remarks: LogPow 2.64 3.78

BCF 3-31 31.00

Potential - low

Mobility in soil

No data available on product.

Safety Data Sheet

F-41 Part A

SECTION 13: Disposal considerations

Disposal methods

Product disposal

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Packaging disposal

Recondition or dispose of empty container in accordance with governmental regulations. Do not reuse empty container without proper cleaning. Empty containers retain product residue (dust, liquid, vapor and/or gases) and can be dangerous. Do not heat or cut container with electric or gas torch.

SECTION 14: Transport information

DOT (US)

UN Number: UN3082

Class: 9

Packing Group: III

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (EPOXY RESIN)

Reportable quantity (RQ):

Marine pollutant: Yes

Poison inhalation hazard:

IMDG

UN Number: UN3082

Class: 9

Packing Group: III

EMS Number:

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (EPOXY RESIN)

IATA

UN Number: UN3082

Class: 9

Packing Group: III

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (EPOXY RESIN)

Safety Data Sheet
F-41 Part A

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Canadian Domestic Substances List (DSL)

Chemical name: Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
CAS number: 25068-38-6

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule weight
CAS number: 25068-38-6

US EPA TSCA public inventory

Chemical name: EPOXYRESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN), average molecule weight
CAS number: 25068-38-6

Canadian Domestic Substances List (DSL)

Chemical name: Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
CAS number: 68609-97-2

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: Alkyl epoxy resin
CAS number: 68609-97-2

US EPA TSCA public inventory

Chemical name: Alkyl epoxy resin
CAS number: 68609-97-2

Canadian Domestic Substances List (DSL)

Chemical name: Oxirane, 2,2'-(2,2-dimethyl-1,3-propanediyl)bis(oxymethylene)]bis-
CAS number: 17557-23-2

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: Component 3
CAS number: 17557-23-2

US EPA TSCA public inventory

Chemical name: Component 3
CAS number: 17557-23-2

Pennsylvania Right To Know Components

Chemical name: 2-FURANMETHANOL, TETRAHYDRO-
CAS number: 97-99-4

Canadian Domestic Substances List (DSL)

Chemical name: 2-Furanmethanol, tetrahydro-
CAS number: 97-99-4

EU Cosmetics Prohibited Substances List, (EC) 2009/1223 Annex II

Chemical name/INN: TETRAHYDROFURFURYL ALCOHOL

Safety Data Sheet

F-41 Part A

CAS number: 97-99-4

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: TETRAHYDROFURFURYL ALCOHOL

CAS number: 97-99-4

US EPA TSCA public inventory

Chemical name: TETRAHYDROFURFURYL ALCOHOL

CAS number: 97-99-4

Canadian Domestic Substances List (DSL)

Chemical name: Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester

CAS number: 41556-26-7

US EPA TSCA public inventory

Chemical name: Component 5

CAS number: 41556-26-7

Canadian Domestic Substances List (DSL)

Chemical name: Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester

CAS number: 82919-37-7

US EPA TSCA public inventory

Chemical name: Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidinyl) ester

CAS number: 82919-37-7

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: TETRAHYDROFURFURYL ALCOHOL

CAS number: 97-99-4

SECTION 16: Other information

16.1 Further information/disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



POLYMER NATION

Safety Data Sheet F-41, -01 Metallic Part B

SECTION 1: Identification

1.1 GHS Product identifier

Product name F-41, -01 Metallic Part B

Product number H5
Brand Polymer Nation

1.2 Other means of identification

Epoxy Hardener

1.3 Recommended use of the chemical and restrictions on use

100% solids clear epoxy hardener for use in resinous flooring applications

1.4 Supplier's details

Name Polymer Nation
Address 405 Oakwood Ave
Waukegan IL 60085
Telephone 847-774-5038

1.5 Emergency phone number

800-424-9300

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2024)

- Acute toxicity, dermal, Cat. 4
- Acute toxicity, inhalation, Cat. 4
- Acute toxicity, oral, Cat. 4
- Eye damage/irritation, Cat. 1
- Eye damage/irritation, Cat. 2A
- Sensitization, respiratory, Cat. 1
- Skin corrosion/irritation, Cat. 1B
- Sensitization, skin, Cat. 1
- Sensitization, skin, Cat. 1A
- Sensitization, skin, Cat. 1B
- Specific target organ toxicity (repeated exposure), Cat. 1
- Specific target organ toxicity (single exposure), Cat. 3

Safety Data Sheet

F-41, -01 Metallic Part B

2.2 GHS label elements, including precautionary statements

Pictograms



Signal word

Danger

Hazard statement(s)

H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H372	Causes damage to organs [organs] through prolonged or repeated exposure [route]

Precautionary statement(s)

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	[In case of inadequate ventilation] wear respiratory protection.
P301+P312	IF SWALLOWED: Call a POISON CENTER /doctor/...if you feel unwell,
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of water/...
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/...
P312	Call a POISON CENTER/doctor/.../ if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see ... on this label).
P330	Rinse mouth.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...
P362+P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to ...

**Safety Data Sheet
F-41, -01 Metallic Part B**

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

1. 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Concentration 25 - 50 % (weight)
EC no. 220-666-8
CAS no. 2855-13-2
Index no. 612-067-00-9

- Acute toxicity, oral, Cat. 4
- Skin corrosion/irritation, Cat. 1B
- Eye damage/irritation, Cat. 1
- Sensitization, skin, Cat. 1A

H302 Harmful if swallowed
H314 Causes severe skin burns and eye damage
H317 May cause an allergic skin reaction
H318 Causes serious eye damage
SCLs/M-factors/ATEs Oral: ATE = 1030 mg/kg bw
Skin Sens. 1A; H317: C ≥ 0,001 %

2. Benzyl alcohol

Concentration 25 - 50 % (weight)
EC no. 202-859-9
CAS no. 100-51-6
Index no. 603-057-00-5

- Acute toxicity, oral, Cat. 4
- Eye damage/irritation, Cat. 2A
- Sensitization, skin, Cat. 1B

H302 Harmful if swallowed
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
SCLs/M-factors/ATEs oral: ATE = 1200 mg/kg bw

3. Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer

Concentration 1 - 10 % (weight)
CAS no. 68609-08-5

4. 4,4'-DIAMINODICYCLOHEXYL METHANE

Concentration 1 - 10 % (weight)
EC no. 217-168-8
CAS no. 1761-71-3

5. Triethanolamine

Concentration 1 - 5 % (weight)
EC no. 203-049-8
CAS no. 102-71-6

**Safety Data Sheet
F-41, -01 Metallic Part B**

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	If inhaled, remove to fresh air.
In case of skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Take victim immediately to hospital.
In case of eye contact	In case of contact, immediately flush eyes with plenty of water for at least 30 minutes. If easy to do, remove contact lens, if worn. Continue rinsing eyes during transport to hospital. Protect unharmed eye. Keep eye wide open while rinsing.
If swallowed	Rinse mouth with water. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Personal protective equipment for first-aid responders	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of immediate medical attention and special treatment needed, if necessary

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Specific hazards arising from the chemical

Burning produces irritant fumes.

Do not allow run-off from fire fighting to enter drains or water courses.

Safety Data Sheet

F-41, -01 Metallic Part B

Benzyl alcohol: Carbon oxides

5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Unsuitable extinguishing media: Do NOT use water jet.

In the event of fire and/or explosion do not breathe fumes.

Prevent fire extinguishing water from contaminating surface water or the ground water system.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Local authorities should be advised if significant spillages cannot be contained.

Do not allow contact with soil, surface or ground water.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Wear personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes.

Use only with adequate ventilation.

Do not breathe vapours/dust.

To avoid spills during handling keep bottle on a metal tray.

Dispose of rinse water in accordance with local and national regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

7.2 Conditions for safe storage, including any incompatibilities

Store in original container.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions.

Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability: No decomposition if stored and applied as directed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Safety Data Sheet

F-41, -01 Metallic Part B

1. Triethanolamine (CAS: 102-71-6 EC: 203-049-8)

PEL (Inhalation): 5 mg/m³; US (Cal/OSHA)

California permissible exposure limits for chemical contaminants (Title 8, Article 107)

TWA (Inhalation): 5 mg/m³; AU (AU/SWA)

Other advisory: Sen

2. Benzyl alcohol (CAS: 100-51-6 EC: 202-859-9)

TWA: 10 ppm

US WEEL

8.2 Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Thermal hazards

No data available

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state

Liquid

Appearance

clear

Color

straw; yellow

Safety Data Sheet

F-41, -01 Metallic Part B

Odor	amine
Odor threshold	ND
Melting point/freezing point	ND
Boiling point or initial boiling point and boiling range	ND
Flammability	ND
Lower and upper explosion limit/flammability limit	ND
Flash point	> 201 F/> 94 C
Auto-ignition temperature	ND
Decomposition temperature	ND
pH	ND
Kinematic viscosity	< 200 cP @ 72 F
Solubility	water - negligible
Partition coefficient n-octanol/water (log value)	ND
Vapor pressure	ND
Evaporation rate	ND
Density and/or relative density	1.02 g/cm3
Relative vapor density	ND

SECTION 10: Stability and reactivity

10.1 Reactivity

None under normal use conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

None under normal use conditions.

10.4 Conditions to avoid

Strong oxidizer

10.5 Incompatible materials

No specific data.

Benzyl alcohol: Strong oxidizing agents

Triethanolamine: Acids, Oxidizing agents

10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, oxides of nitrogen, other undetermined compounds

Benzyl alcohol: Other decomposition products - No data available

In the event of fire: see section 5

Triethanolamine: Hazardous decomposition products formed under fire conditions. - Carbon oxides, Nitrogen oxides (NOx)

Other decomposition products - No data available

In the event of fire: see section 5

**Safety Data Sheet
F-41, -01 Metallic Part B**

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Benzyl alcohol: LD50 Oral - Rat - 1,230 mg/kg

Remarks: Behavioral:Somnolence (general depressed activity). Behavioral:Excitement. Behavioral:Coma.

LD50 Oral - Rat - male - 1,620 mg/kg

Dermal: No data available

No data available

Triethanolamine

LD50 Oral - Mouse - 5,846 mg/kg

Remarks: Behavioral:Convulsions or effect on seizure threshold. Diarrhoea Kidney, Ureter, Bladder:Other changes.

LD50 Oral - Rat - 5,530 mg/kg

Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Lacrimation. Diarrhoea Skin and Appendages: Other: Hair.

LD50 Oral - Rabbit - 2,200 mg/kg

LD50 Oral - Guinea pig - 2,200 mg/kg

LD50 Skin - Rabbit - >22.5 g/kg

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

LD50 Oral - Rat - 1030 mg/kg

LD50 Skin - Rat - >2000 mg/kg

LC50 Inhalation - Rat - 5.01 mg/l - 4 h

Skin corrosion/irritation

Causes severe burns

Benzyl alcohol: Benzyl alcohol

OECD Test Guideline 404 Skin - Rabbit - 24 h

Result: No skin irritation

Serious eye damage/irritation

Causes serious eye damage.

Benzyl alcohol: Benzyl alcohol

OECD Test Guideline 405 Eyes - Rabbit - 24 h

Result: Eye irritation

Respiratory or skin sensitization

Skin sensitisation-May cause an allergic skin reaction.

Respiratory sensitisation-Not classified based on available information.

Benzyl alcohol: No data available.

Germ cell mutagenicity

Not classified based on available information.

Benzyl alcohol: No data available.

Safety Data Sheet

F-41, -01 Metallic Part B

Carcinogenicity

Not classified based on available information.

Benzyl alcohol: IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Benzyl alcohol: No data available.

Summary of evaluation of the CMR properties

Benzyl alcohol: No data available.

Specific target organ toxicity (STOT) - single exposure

Not classified based on available information.

Benzyl alcohol: No data available.

Specific target organ toxicity (STOT) - repeated exposure

Not classified based on available information.

Benzyl alcohol: No data available.

Aspiration hazard

Not classified based on available information.

Benzyl alcohol: No data available.

SECTION 12: Ecological information

Toxicity

Benzyl Alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l

End point: mortality

Exposure time: 96 h

Test Type: static test

Analytical monitoring: no

GLP: no

Toxicity to fish (Chronic toxicity): NOEC: 48.897 mg/l

Exposure time: 30 d

Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Safety Data Sheet

F-41, -01 Metallic Part B

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 110 mg/l
End point: mortality
Exposure time: 96 h
Test Type: semi-static test

Benzyl alcohol: Benzyl alcohol
LC50 - Lepomis macrochirus (bluegill) - 10 mg/l - 96 h

Benzyl alcohol
LC50 - Pimephales promelas (fathead minnow) - 460 mg/l - 96 h

Benzyl alcohol
EC50 - Daphnia magna (water flea) - 55 mg/l - 24 h

Benzyl alcohol
LC50 Percutaneous - Lepomis macrochirus (Bluegill) - 10 mg/l - 96 h

Benzyl alcohol
LC50 Percutaneous - Pimephales promelas (fathead minnow) - 460 mg/l - 96 h

Persistence and degradability

benzyl alcohol:
Biodegradability : aerobic
Inoculum: activated sludge
Concentration: 100 mg/l
Biochemical oxygen demand
Result: Readily biodegradable.
Biodegradation: 95 %
Exposure time: 14 d
Method: OECD Test Guideline 301C
Stability in water : Degradation half life: 9 yr

3-aminomethyl-3,5,5-trimethylcyclohexylamine:
Biodegradability : aerobic
Inoculum: activated sludge
Concentration: 6.9 mg/l
Result: Not readily biodegradable.
Biodegradation: 8 %
Exposure time: 28 d
Method: Tested according to Directive 92/69/EEC.
Stability in water : Degradation half life (DT50): > 1 yr (25 °C) pH: 4 - 9
Hydrolysis: < 10 % at 50 °C(5 d)

Benzyl alcohol: Benzyl alcohol
Biotic/Aerobic - Exposure time 28 d
Result: Result: 92 - 96 % - Readily biodegradable

Benzyl alcohol
Aerobic Biochemical oxygen demand - Exposure time 7 d
Result: Result: 92 - 96 % - Readily biodegradable

Safety Data Sheet

F-41, -01 Metallic Part B

(OECD Test Guideline 301C)

Bioaccumulative potential

benzyl alcohol:

Bioaccumulation : Bioconcentration factor (BCF): 1.37

Remarks: Bioaccumulation is unlikely.

Partition coefficient: noctanol/water: log Pow: 1.05 (68 °F / 20 °C)

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 76.22

Remarks: Bioaccumulation is unlikely.

Partition coefficient: noctanol/water: log Pow: 0.99 (73 °F / 23 °C)

pH: 6.34

Benzyl alcohol: No data available.

Mobility in soil

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Mobility : Medium: Air

Content: 0.02 %

Method: Calculation, Mackay Level I Fugacity Model

Medium: Water

Content: 99.83 %

Medium: Soil

Content: 0.08 %

Medium: Sediment

Content: 0.08 %

Distribution among environmental compartments: Koc: 928, log Koc: 2.97

Benzyl alcohol: No data available.

Results of PBT and vPvB assessment

Benzyl alcohol: PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects

Benzyl alcohol: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant

Safety Data Sheet

F-41, -01 Metallic Part B

with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Packaging disposal

Recondition or dispose of empty container in accordance with governmental regulations. Do not reuse empty container without proper cleaning. Empty containers retain product residue (dust, liquid, vapor and/or gases) and can be dangerous. Do not heat or cut container with electric or gas torch.

SECTION 14: Transport information

DOT (US)

UN Number: UN2735

Class: 8

Packing Group: II

Proper Shipping Name: Amines, liquid, corrosive, n.o.s. (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE)

Reportable quantity (RQ):

Marine pollutant: no

Poison inhalation hazard:

IMDG

UN Number: UN2735

Class: 8

Packing Group: II

EMS Number:

Proper Shipping Name: Amines, liquid, corrosive, n.o.s. (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE)

IATA

UN Number: UN2735

Class: 8

Packing Group: II

Proper Shipping Name: Amines, liquid, corrosive, n.o.s. (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Canadian Domestic Substances List (DSL)

Chemical name: Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-
CAS number: 2855-13-2

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE
CAS number: 2855-13-2

US EPA TSCA public inventory

Chemical name: 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE
CAS number: 2855-13-2

**Safety Data Sheet
F-41, -01 Metallic Part B**

Water hazard class (WGK, Germany)

Chemical name: 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE, CAS number: 2855-13-2
WGK hazard class: WGK 1 - Slightly hazardous to water

Pennsylvania Right To Know Components

Chemical name: BENZENEMETHANOL
CAS number: 100-51-6

Canadian Domestic Substances List (DSL)

Chemical name: Benzenemethanol
CAS number: 100-51-6

Water hazard class (WGK, Germany)

Chemical name: Benzyl alcohol, CAS number: 100-51-6
WGK hazard class: WGK 1 - Slightly hazardous to water

EU Cosmetics Allowed preservatives List, (EC) 2009/1223 Annex V

Chemical name: Benzyl alcohol
CAS number: 100-51-6

EU Cosmetics Restricted Substances List, (EC) 2009/1223 Annex III

Chemical name/INN: Benzyl alcohol
CAS number: 100-51-6

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: Benzyl alcohol
CAS number: 100-51-6

US EPA TSCA public inventory

Chemical name: Benzyl alcohol
CAS number: 100-51-6

Canadian Domestic Substances List (DSL)

Chemical name: Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer
CAS number: 68609-08-5

US EPA TSCA public inventory

Chemical name: Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer
CAS number: 68609-08-5

Pennsylvania Right To Know Components

Chemical name: ETHANOL, 2,2',2"-NITRILOTRIS-
CAS number: 102-71-6

Canadian Domestic Substances List (DSL)

Chemical name: Ethanol, 2,2',2"-nitrilotris-

Safety Data Sheet

F-41, -01 Metallic Part B

CAS number: 102-71-6

Water hazard class (WGK, Germany)

Chemical name: Triethanolamine, CAS number: 102-71-6
WGK hazard class: WGK 1 - Slightly hazardous to water

US EPA TSCA public inventory

Chemical name: Triethanolamine
CAS number: 102-71-6

Canadian Domestic Substances List (DSL)

Chemical name: Cyclohexanamine, 4,4'-methylenebis-
CAS number: 1761-71-3

US EPA TSCA public inventory

Chemical name: 4,4'-DIAMINODICYCLOHEXYL METHANE
CAS number: 1761-71-3

Water hazard class (WGK, Germany)

Chemical name: 4,4'-DIAMINODICYCLOHEXYL METHANE, CAS number: 1761-71-3
WGK hazard class: WGK 3 - Extremely hazardous to water

New Jersey Right To Know Components

Common name: ISOPHORONEDIAMINE
CAS number: 2855-13-2

SARA 302 Components

No chemicals in this material [Benzyl alcohol] are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material [Benzyl alcohol] does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard for: Benzyl alcohol.

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: BENZYL ALCOHOL
CAS number: (none)

SARA 302 Components

No chemicals in this material [Triethanolamine] are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material [Triethanolamine] does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Safety Data Sheet

F-41, -01 Metallic Part B

SARA 311/312 Hazards

Chronic Health Hazard for: Triethanolamine.

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: TRIETHANOLAMINE

CAS number: 102-71-6

SECTION 16: Other information

16.1 Further information/disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



POLYMER NATION

Safety Data Sheet F-61 Part A

SECTION 1: Identification

1.1 GHS Product identifier

Product name	F-61 Part A
Product number	P1
Brand	Polymer Nation

1.2 Other means of identification

Polyaspartic Resin

1.3 Recommended use of the chemical and restrictions on use

High solids clear polyaspartic resin for use in resinous flooring applications

1.4 Supplier's details

Name	Polymer Nation
Address	405 Oakwood Ave
	Waukegan IL 60085
Telephone	847-774-5038

1.5 Emergency phone number

800-424-9300

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2024)

- Sensitization, skin, Cat. 1
- Hazardous to the aquatic environment, long-term (chronic), Cat. 3

2.2 GHS label elements, including precautionary statements

Pictograms



Signal word

Warning

Safety Data Sheet

F-61 Part A

Hazard statement(s)	
H317	May cause an allergic skin reaction
H412	Harmful to aquatic life with long lasting effects
Precautionary statement(s)	
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P272	Contaminated work clothing must not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water/...
P321	Specific treatment (see ... on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P501	Dispose of contents/container to ...

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

1. bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane

Concentration	40 - 60 % (weight)
EC no.	412-060-9
CAS no.	136210-32-7
Index no.	607-350-00-9

- Sensitization, skin, Cat. 1
- Hazardous to the aquatic environment, long-term (chronic), Cat. 3

H317	May cause an allergic skin reaction
H412	Harmful to aquatic life with long lasting effects

2. Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester

Concentration	15 - 30 % (weight)
EC no.	429-270-1
CAS no.	136210-30-5
Index no.	607-521-00-8

- Sensitization, skin, Cat. 1
- Hazardous to the aquatic environment, long-term (chronic), Cat. 3

H317	May cause an allergic skin reaction
H412	Harmful to aquatic life with long lasting effects

3. Propanol, 1(or 2)-(2-methoxymethylethoxy)-, acetate

Concentration	10 - 30 % (weight)
CAS no.	88917-22-0

Safety Data Sheet

F-61 Part A

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
In case of skin contact	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician
	Rinse with plenty of water. Get medical attention if irritation develops and persists.
In case of eye contact	Flush eyes with water as a precaution.
	Rinse thoroughly with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
If swallowed	Rinse mouth. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call a poison center or doctor if you feel unwell.
	Acute and delayed symptoms and effects: Harmful if swallowed. May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of immediate medical attention and special treatment needed, if necessary

No data available

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Specific hazards arising from the chemical

Carbon oxides

5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

Safety Data Sheet

F-61 Part A

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel). Keep in suitable, closed containers for disposal.

Sweep up and shovel. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols.

Use personal protective equipment as required. Keep container closed when not in use. Never return spills in original containers for re-use. Keep out of the reach of children.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester (CAS: 136210-30-5 EC: 429-270-1)
2. bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane (CAS: 136210-32-7 EC: 412-060-9)
3. Propanol, 1(or 2)-(2-methoxymethylethoxy)-, acetate (CAS: 88917-22-0)

8.2 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Face shield and/or safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Safety Data Sheet

F-61 Part A

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Thermal hazards

No data available

Environmental exposure controls

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state	Liquid
Appearance	clear
Odor	mild solvent
Odor threshold	ND
Melting point/freezing point	ND
Boiling point or initial boiling point and boiling range	200 C
Flammability	ND
Lower and upper explosion limit/flammability limit	
Flash point	ND
Auto-ignition temperature	ND
Decomposition temperature	ND
pH	ND
Kinematic viscosity	< 500 cP
Solubility	ND
Partition coefficient n-octanol/water (log value)	ND
Vapor pressure	ND
Evaporation rate	ND
Density and/or relative density	1.038
Relative vapor density	ND

SECTION 10: Stability and reactivity

10.1 Reactivity

None under normal use conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

None under normal use conditions.

10.4 Conditions to avoid

None under normal use conditions.

Avoid storing in direct sunlight and avoid extremes of temperature.

Heat, flames and sparks.

Safety Data Sheet

F-61 Part A

10.5 Incompatible materials

Strong oxidizing agents, acids, and isocyanates

10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, oxides of nitrogen, other undetermined compounds

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester

LD50 Oral - Rat - >2,000 mg/kg

LD50 Skin - Rat - >2,000 mg/kg

LC50 Inhalation - Rat - >3,224 mg/l - 4 h

bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane

LD50 Oral - Rat - >2,000 mg/kg

LC50 Inhalation - Rat - >4,224 mg/l - 4 h

LD50 Skin - Rat - >2,000 mg/kg

Propanol, 1(or 2)-(2-methoxymethylmethoxy)-, acetate

LD50 Oral - >5,000 mg/kg

LD50 Skin - >2,000 mg/kg

LC50 Inhalation - >20 mg/l

Skin corrosion/irritation

Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester

Result: slight irritant

bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane

Rabbit

Result: slight irritant

Serious eye damage/irritation

Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester

Rabbit

Result: slightly irritating

Respiratory or skin sensitization

Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester

Rat

Result: slight irritant

Germ cell mutagenicity

Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester

Mutagenicity in vitro

Result: No indication of mutagenic effects

Carcinogenicity

Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester

Result: No carcinogenic substances as defined by IARC, NTP and/or OSHA

Safety Data Sheet

F-61 Part A

Reproductive toxicity

bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane
Oral - Rat - 1,000 mg/kg

Specific target organ toxicity (STOT) - single exposure

Based on available data, classification data are not met

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, classification data are not met

Aspiration hazard

May be harmful if swallowed and enters airways

SECTION 12: Ecological information

Toxicity

bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane
LC50 - Danio rerio (zebra fish) - 66 mg/l - 96 h
EC50 - Daphnia magna (water flea) - 88.6 mg/l - 48 h
EC50 - Scenedesmus subspicatus (green algae) - 113 mg/l - 72 h

Persistence and degradability

13 %, Exposure time: 28 d, i.e. not readily degradable
Ecotoxicological reports on a comparable product
0 %, Exposure time: 28 d, i.e. not inherently degradable
Ecotoxicological studies of the product

Bioaccumulative potential

value calculated, 1,872 BCF

The substance hydrolyzes rapidly in water. An accumulation in aquatic organisms is not to be expected.

Mobility in soil

bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane
Adsorption/Soil
log Koc value: 4,2 - 5,1
Method: EU Method C.19

Results of PBT and vPvB assessment

No data available.

Other adverse effects

No data available.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Waste disposal should be in accordance with existing federal, state and local environmental control laws.

Packaging disposal

Recondition or dispose of empty container in accordance with governmental regulations. Do not reuse empty container without proper cleaning. Empty containers retain product residue (dust, liquid, vapor and/or gases) and can be dangerous. Do not heat or cut container with electric or gas torch.

Safety Data Sheet

F-61 Part A

SECTION 14: Transport information

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Canadian Domestic Substances List (DSL)

Chemical name: DL-Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, tetraethyl ester
CAS number: 136210-32-7

Chemical name: Aspartic acid N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, tetraethyl ester
CAS number: 136210-30-5

Chemical name: Propanol, 1(or 2)-(2-methoxymethylethoxy)-, acetate
CAS number: 88917-22-0

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane
CAS number: 136210-32-7

Chemical name: Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester
CAS number: 136210-30-5

US EPA TSCA public inventory

Chemical name: bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane
CAS number: 136210-32-7

Chemical name: Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester
CAS number: 136210-30-5

Chemical name: Propanol, 1(or 2)-(2-methoxymethylethoxy)-, acetate
CAS number: 88917-22-0

SECTION 16: Other information

16.1 Further information/disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



POLYMER NATION

Safety Data Sheet F-60,61,70,71,80,81 Part B

SECTION 1: Identification

1.1 GHS Product identifier

Product name	F-60,61,70,71,80,81 Part B
Product number	ISO4/ISO4 LV2
Brand	Polymer Nation
Substance name	HEXAMETHYLENE DIISOCYANATE

1.2 Other means of identification

Isocyanate Hardener

1.3 Recommended use of the chemical and restrictions on use

Hardener component for polyaspartic resin; for use in resinous flooring applications

1.4 Supplier's details

Name	Polymer Nation
Address	405 Oakwood Ave
	Waukegan IL 60085
Telephone	847-774-5038

1.5 Emergency phone number

800-424-9300

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2024)

- Acute toxicity, inhalation, Cat. 3
- Eye damage/irritation, Cat. 2A
- Sensitization, respiratory, Cat. 1
- Skin corrosion/irritation, Cat. 2
- Sensitization, skin, Cat. 1
- Specific target organ toxicity (single exposure), Cat. 3

2.2 GHS label elements, including precautionary statements

Pictograms



Signal word

Danger

**Safety Data Sheet
F-60,61,70,71,80,81 Part B**

Hazard statement(s)

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H331	Toxic if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

Precautionary statement(s)

P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear eye protection/face protection/protective gloves.
P284	[In case of inadequate ventilation] wear respiratory protection.
P302+P352	IF ON SKIN: Wash with plenty of water/...
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P311	Call a POISON CENTER/doctor/...
P312	Call a POISON CENTER/doctor/.../ if you feel unwell.
P321	Specific treatment (see ... on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...
P362+P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to ...

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name	HEXAMETHYLENE DIISOCYANATE
Other names / synonyms	Hexamethylendiisocyanatoligomere, Allophanat; Hexamethylendiisocyanatoligomere, Allophanat; Hexamethylendiisocyanatoligomere, Allophanat; Hexamethylendiisocyanatoligomere, Allophanat; Hexamethylendiisocyanatoligomere, Allophanat; Hexane, 1,6-diisocyanato-, homopolymer; Hexamethylendiisocyanatoligomere, Isocyanurat

Hazardous components

1. Hexamethylendiisocyanatoligomere, Isocyanurat

Concentration	95 - 100 % (weight)
EC no.	931-274-8
CAS no.	28182-81-2

**Safety Data Sheet
F-60,61,70,71,80,81 Part B**

2. HEXAMETHYLENE DIISOCYANATE

Concentration < 0.1 % (weight)
EC no. 212-485-8
CAS no. 822-06-0
Index no. 615-011-00-1

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

If inhaled Move to an area free from further exposure. Extreme asthmatic reactions that may occur in sensitized persons can be life threatening. Get medical attention immediately. Administer oxygen or artificial respiration as needed. Asthmatic symptoms may develop and may be immediate or delayed up to several hours.

In case of skin contact If direct skin contact with isocyanates occurs, immediately remove contaminated clothing and shoes. Wipe off the isocyanate product from the skin using dry towels or other similar absorbent fabric. If readily available, apply a polyglycol-based cleanser (e.g. SKC, Inc. (SKC) D-TAM™ Skin Cleanser) or corn oil. Wash with soap and warm water and pat dry. If a polyglycol-based cleanser is not available, wash with soap and warm water for 15 minutes. If available, use a wipe test pad to verify decontamination is complete (e.g. SKC SWYPE™). Get medical attention if irritation develops. Discard or wash contaminated clothing before reuse.

In case of eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Use lukewarm water if possible. Use fingers to ensure that eyelids are separated and that the eye is being irrigated. Then remove contact lenses, if easily removable, and continue eye irrigation for not less than 15 minutes. Get medical attention if irritation develops.

If swallowed Do NOT induce vomiting. Wash mouth out with water. Do not give anything by mouth to an unconscious person. Get medical attention.

4.2 Most important symptoms/effects, acute and delayed

Acute: Isocyanate vapors or mist at concentrations above the exposure limits or guidelines can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) with symptoms of runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing difficulty). Persons with a preexisting, nonspecific bronchial hyperreactivity can respond to concentrations below the exposure limits or guidelines with similar symptoms as well as asthma attack or asthma-like symptoms. Exposure well above the exposure limits or guidelines may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). Chemical or hypersensitivity pneumonitis, with flu-like symptoms (e.g. fever, chills), has also been reported. These symptoms can be delayed up to several hours after exposure. These effects are usually reversible.

Safety Data Sheet

F-60,61,70,71,80,81 Part B

May cause skin irritation with symptoms of reddening, itching, and swelling. Can cause sensitization. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Cured material is difficult to remove.

May cause eye irritation with symptoms of reddening, tearing, stinging, and swelling. May cause temporary corneal injury. Vapor or aerosol may cause irritation with symptoms of burning and tearing.

May cause irritation of the digestive tract; Symptoms may include abdominal pain, nausea, vomiting, and diarrhea.

Delayed: Symptoms affecting the respiratory tract can also occur several hours after overexposure.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Eyes: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic/steroid preparation as needed. Workplace vapors could produce reversible corneal epithelial edema impairing vision.

Skin: This compound is a skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn.

Ingestion: Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of the compound.

Inhalation: Treatment is essentially symptomatic. An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanate.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Foam, water spray for large fires

5.2 Specific hazards arising from the chemical

By Fire and High Heat: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke., Hydrogen cyanide, Isocyanate, Isocyanic Acid, Other undetermined compounds

5.3 Special protective actions for fire-fighters

Unsuitable Extinguishing Media: High volume water jet

Fire Fighting Procedure

Firefighters should wear NFPA compliant structural firefighting protective equipment, including self-contained breathing apparatus and NFPA compliant helmet, hood, boots and gloves. Avoid contact with product. Decontaminate equipment and protective clothing prior to reuse. During a fire, isocyanate vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. Exposure to heated diisocyanate can be extremely dangerous.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear necessary personal protective equipment (PPE) as specified in the SDS or the site emergency response plan. Ventilate and remove ignition sources.

Implement site emergency response plan. Evacuate non-emergency personnel. The magnitude of the evacuation depends upon the quantity released, site conditions, and the ambient temperature. Isolate the area and prevent access of unauthorized personnel. Notify management.

6.3 Methods and materials for containment and cleaning up

Control the source of the leak. Contain the released material by damming, diking, retaining, or diverting into an appropriate containment area. Absorb or pump off as much of the spilled material as possible. When using absorbent, completely cover the spill area with suitable absorbent material (e.g., vermiculite, kitty litter, Oil-Dri®, etc...). Allow for the absorbent material

Safety Data Sheet

F-60,61,70,71,80,81 Part B

to absorb the spilled liquid. Shovel the absorbent material into an approved metal container (i.e., 55-gallon salvage drum). Do not fill the container more than 2/3 full to allow for expansion, and do not tighten the lid on the container. Repeat application of absorbent material until all liquid has been removed from the surface. For spills involving a solid product, remove mechanically (sweep up, vacuum, shovel etc.) and collect and place into an approved metal container.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Do not breathe vapors, mists, or dusts. Use adequate ventilation to keep airborne isocyanate levels below the exposure limits. Wear respiratory protection if material is heated, sprayed, used in a confined space, or if the exposure limit is exceeded. Warning properties (irritation of the eyes, nose and throat or odor) are not adequate to prevent overexposure from inhalation. This material can produce asthmatic sensitization upon either single inhalation exposure to a relatively high concentration or upon repeated inhalation exposures to lower concentrations. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must not be exposed to vapor or spray mist. Avoid contact with skin and eyes. Wear appropriate eye and skin protection. Wash thoroughly after handling. Do not breathe smoke and gases created by overheating or burning this material. Decomposition products can be highly toxic and irritating. Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected.

7.2 Conditions for safe storage, including any incompatibilities

Store separate from food products.

Employee education and training in the safe use and handling of this product are required under the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Substances to Avoid

Water, Amines, Strong bases, Alcohols, Copper alloys

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Hexamethylene diisocyanate (CAS: 822-06-0)

TWA (Inhalation): See Isocyanates, all ppm; AU (AU/SWA)

Other advisory: Sen

8.2 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, gas, etc.) below recommended exposure limits.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Safety Data Sheet

F-60,61,70,71,80,81 Part B

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state	Liquid
Appearance	Clear
Color	colorless
Odor	nearly odorless
Odor threshold	ND
Melting point/freezing point	ND
Boiling point or initial boiling point and boiling range	ND
Flammability	ND
Lower and upper explosion limit/flammability limit	ND
Flash point	158 C/316 F
Auto-ignition temperature	445 C/833 F
Decomposition temperature	ND
pH	ND
Kinematic viscosity	700-2500 cP
Solubility	Insoluble in water
Partition coefficient n-octanol/water (log value)	ND
Vapor pressure	5.2 x 10^-9 mmHg @ 68 F
Evaporation rate	ND
Density and/or relative density	1.17
Relative vapor density	ND

SECTION 10: Stability and reactivity

10.1 Reactivity

None under normal use conditions.

10.2 Chemical stability

Stable under normal conditions of use and storage.

10.3 Possibility of hazardous reactions

Contact with moisture, other materials that react with isocyanates, or temperatures above 350 F (177 C), may cause polymerization. Moisture (water and high humidity) or high heat (temperatures greater than 350 F (177C)) can cause pressure build-up with possible explosive rupture.

10.4 Conditions to avoid

Heat, flames and sparks. Protect from freezing.

10.5 Incompatible materials

Water, Amines, Strong bases, Alcohols, Copper alloys

Safety Data Sheet

F-60,61,70,71,80,81 Part B

10.6 Hazardous decomposition products

By Fire and High Heat: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke., Hydrogen cyanide, Isocyanate, Isocyanic Acid, Other undetermined compounds

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Hexamethylendiisocyanatoligomere, Isocyanurat

LD50 Oral - Rat - >2,500 mg/kg

LC50 Inhalation - Rat - 0.39-0.543 mg/L - 4 hrs

LD50 Skin - Rat - >2,000 mg/kg

Skin corrosion/irritation

Hexamethylendiisocyanatoligomere, Isocyanurat

Rabbit - 4 hrs

Result: slight irritant

Serious eye damage/irritation

Hexamethylendiisocyanatoligomere, Isocyanurat

Rabbit

Result: slight irritant

Respiratory or skin sensitization

Hexamethylendiisocyanatoligomere, Isocyanurat

Guinea pig

Result: positive

Germ cell mutagenicity

Genetic Toxicity in Vitro:

Salmonella/microsome test (Ames test): No indication of mutagenic effects. (Metabolic Activation: with/without)

Chromosome aberration test in vitro: negative (Chinese hamster V79 cell line, Metabolic Activation: with/without)

Point mutation in mammalian cells (HPRT test): negative (Chinese hamster ovary (CHO) cells, Metabolic Activation: with/without)

Carcinogenicity

No carcinogenic substances as defined by IARC, NTP and/or OSHA

Reproductive toxicity

Available data show no indications for reproductive toxicity.

Specific target organ toxicity (STOT) - single exposure

No data available

Specific target organ toxicity (STOT) - repeated exposure

90 d, Inhalative: NOAEL: 3.3, (rat, male/female, 6 hours a day, 5 days a week)

Irritation to lungs and nasal cavity. Evidence of damage to organs other than the organs of respiration was not found.

Aspiration hazard

May be harmful if swallowed and enters airways

**Safety Data Sheet
F-60,61,70,71,80,81 Part B**

SECTION 12: Ecological information

Toxicity

LC50: > 100 mg/l (Danio rerio (zebra fish), 96 h)
EC50: > 100 mg/l (Daphnia magna (Water flea), 48 h)
ErC50: > 1,000 mg/l, (scenedesmus subspicatus, 72 h)
EC50: 3,828 mg/l, (activated sludge, 3 h)

Persistence and degradability

aerobic, 1 %, Exposure time: 28 d, i.e. not readily degradable
aerobic, 0 %, Exposure time: 28 d, i.e. not readily degradable

Bioaccumulative potential

3.2 BCF

An accumulation in aquatic organisms is not to be expected.

367.7 BCF

An accumulation in aquatic organisms is not to be expected. Studies of hydrolysis products.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Packaging disposal

Containers that are empty as defined by RCRA (40 CFR part 261.7), may retain product residue; observe all precautions for product. Do not grind, torch cut, weld or heat an empty container that once held an isocyanate-containing product; highly toxic vapors or gases are formed.

SECTION 14: Transport information

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

US EPA TSCA public inventory

Chemical name: Hexamethylendiisocyanatoligomere, Allophanat
CAS number: 28182-81-2

Canadian Domestic Substances List (DSL)

Chemical name: Hexane, 1,6-diisocyanato-, homopolymer
CAS number: 28182-81-2

Safety Data Sheet

F-60,61,70,71,80,81 Part B

US EPA TSCA public inventory

Chemical name: Hexamethylendiisocyanatoligomere, Isocyanurat
CAS number: 28182-81-2

Massachusetts Toxic Use Reduction Act (TURA) list

Chemical name: Hexamethylene-1,6-diisocyanate
CAS number: 822-06-0

New Jersey Right To Know Components

Common name: HEXAMETHYLENE DIISOCYANATE
CAS number: 822-06-0

Canadian Domestic Substances List (DSL)

Chemical name: Hexane, 1,6-diisocyanato-
CAS number: 822-06-0

EU Table of Harmonised Entries (Annex VI to CLP)

Chemical name: HEXAMETHYLENE DIISOCYANATE
CAS number: 822-06-0

US EPA TSCA public inventory

Chemical name: HEXAMETHYLENE DIISOCYANATE
CAS number: 822-06-0

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: HEXAMETHYLENE DIISOCYANATE
CAS number: 822-06-0

Massachusetts Toxic Use Reduction Act (TURA) list

Chemical name: Hexamethylene-1,6-diisocyanate
CAS number: 822-06-0

New Jersey Right To Know Components

Common name: HEXAMETHYLENE DIISOCYANATE
CAS number: 822-06-0

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: HEXAMETHYLENE DIISOCYANATE
CAS number: 822-06-0

SECTION 16: Other information

16.1 Further information/disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.